



An ISO 9001:2008 & 14001:2004 Certified Co.

PRODUCT OVERVIEW

It is a polymer base material, used as cement waterproofing for high bonding to surface and gives strength. This is crack & water proofing ability. Overall it reduces the Maintenance of the walls and increases the life of the wall/buildings.

PRODUCT BENEFITS	PACKING
<ul style="list-style-type: none"> 100% Water Proof High Adhesion Admixture 	<ul style="list-style-type: none"> 200 Ltrs. 20 Ltrs. 5 Ltrs. 1 Ltrs. 500 MI 200 MI <p>Shelf life : 3years from the date of manufacture in original tight closed containers & to be stored away from direct sunlight and excessive heat.</p>

TECHNICAL SPECIFICATION			
Properties	Viscosity	Appearance	Density
<ul style="list-style-type: none"> » Water Soluble Before Drying » Air Drying & Curing » Single Component 	16.66 Sec.	Milky White	1.007 Kg/Ltr
Complete Curing			
	24 Hours @ 25°C		
Water Permeability	Adhesion Strength	Surface Drying Time	
Negligible	Excellent	20 Min @ 25°C	
Sofetning Point	Storage & Pot Life	Coverage	
90°C	36 Months Store Between 10 To 35	35 Sqfts/Ltr	

Note : The Product material can be renewed by the company for the betterment at anytime without any notice/information.

SURFACE PREPARATION

- Clean the Surface thoroughly, as it should be free from dust, oil, etc.
- After cleaning wash the surface with water.



APPLICATION PROCEDURES

As ADMIXTURE

- » Add 5% CCP Mix Plus of water (eg. add 10 ltr of CCP Mix Plus in 200 Ltr of water.)
- » Stir it thoroughly before use.
- » Use this chemically prepared water for preparing water resistant mortar/plaster.

As COATING

- » Use **CCP Mix Plus** as base Coating (In each process of waterproofing use this as base coat).
- » Ratio of preparing **CCP Mix Plus** (1.5 Kg Cement + 400 MI water) Stir properly after mixing add 1 Ltr. CCP Mix for best results.
- » After preparing **CCP Mix Plus**, apply 2 coats and let the surface to be cured for 12-18 hours before use.

Product Mixing Ratio (by volume)

Single pack

Thinner / Cleaning Solvent

Water

Caution

The applicators and operators must be trained, experienced and have the understanding and equipment to mix/stir and apply the coatings correctly and according to Nusshar technical protocol. Applicators and operators shall use appropriate personal protection when using these products.

Health and safety

Please study the safety precautions mentioned on the container. Apply the products under well ventilated conditions. Ensure that spray mist is not inhaled and skin contact with the product should be avoided. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. If the eyes feel any burning sensation then they should be flushed with ample water and the Doctor should be immediately consulted.

Note: We do not undertake any legal obligation for the product as its proper application is equally important. We accept no legal responsibility for the work done even by trained applicators as we have no control over what they are actually doing on the site. The consumer has to first satisfy himself/herself by observing work done by us & by visiting our display gallery.

All subject to the jurisdiction of courts in Jodhpur, Rajasthan.