



An ISO 9001:2008 & 14001:2004 Certified Co.

PRODUCT OVERVIEW

Mother Coat is a polymer based interior paint which is being used for 100% Water Proofing and up to 85% of heat reflectivity with silky finish.

| PRODUCT BENEFITS | PACKING |
|---|--|
| <ul style="list-style-type: none"> Matt Finish Water Proof Anti Bacterial | <ul style="list-style-type: none"> 20 Kg. 10 Kg. 4 Kg. 1 Ltr. <p>Shelf life : 3years from the date of manufacture in original tight closed containers & to be stored away from direct sunlight and excessive heat.</p> |



TECHNICAL SPECIFICATION

| Properties | Viscosity | Final Finish | Density |
|--|------------------------------------|----------------------------|------------|
| <ul style="list-style-type: none"> » Water Soluble Before Drying » Air Drying & Curing » Single Component | Semi Paste | Matt (Satin Finish) | 1.48 gm/cc |
| Complete Curing | | | |
| | 48 Hours @ 25°C | | |
| Water Permeability | Adhesion Strength | Surface Drying Time | |
| Negligible | Excellent | 20 Min @ 25°C | |
| Softening Point | Storage & Pot Life | Coverage | |
| 90°C | 36 Months Store Between 10 To 35 | 60-70 Sq ft (2 Coats) | |

Note : The Product material can be renewed by the company for the betterment at anytime without any notice/information.

SURFACE PREPARATION

- Clean the Surface thoroughly, as it should be free from dust, oil, etc.
- Remove existing Paint Layer/ Coating before applying "Mother Coat"
- It is recommended to use wire brush followed by sanding with emery.
- For Re-Paint work it is recommended to use Nushar's Old Paint Fixer to save time & labour



APPLICATION PROCEDURES

PROCESS OF APPLYING

- » Apply two coats of True Aegis Wall Putty.
- » After putty is dried apply one coat of primer with 40% water dilution.
- » After curing of primer apply two coats of Mother Coat Paint with the help of brush and roller.
- » Air bubbles or roller marks should be scrubbed before final coat.

Final coat should be thin for better finish.

Let the final coat cure for 20-40 hours.

Product Mixing Ratio (by volume)

Single pack

Thinner / Cleaning Solvent

Water

Caution

The applicators and operators must be trained, experienced and have the understanding and equipment to mix/stir and apply the coatings correctly and according to Nushar technical protocol. Applicators and operators shall use appropriate personal protection when using these products.

Health and safety

Please study the safety precautions mentioned on the container. Apply the products under well ventilated conditions. Ensure that spray mist is not inhaled and skin contact with the product should be avoided. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. If the eyes feel any burning sensation then they should be flushed with ample water and the Doctor should be immediately consulted.

Note: We do not undertake any legal obligation for the product as its proper application is equally important. We accept no legal responsibility for the work done even by trained applicators as we have no control over what they are actually doing on the site. The consumer has to first satisfy himself/herself by observing work done by us & by visiting our display gallery.

All subject to the jurisdiction of courts in Jodhpur, Rajasthan.